

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® STANDARD ULTRA HARDENER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Hardener
Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : HUNTSMAN ADVANCED MATERIALS (UK) LIMITED
Address : Ickleton Road, Duxford, Cambridgeshire
CB22 4XQ United Kingdom
Telephone : +41 61 299 20 41
E-mail address of person : Global_Product_EHS_AdMat@huntsmman.com
responsible for the SDS

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

| | |
|--|--|
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Long-term (chronic) aquatic hazard, Category 2 | H411: Toxic to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Hazard pictograms

:



Signal word

: Danger

Hazard statements

| | |
|------|--|
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

| | |
|------|---|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read carefully and follow all instructions. |

Prevention:

| | |
|------|--|
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/ eye protection/ face protection. |

Response:

| | |
|---------------------------|--|
| P305 + P351 + P338 + P310 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. |
| P391 | Collect spillage. |

Disposal:

| | |
|------|--|
| P501 | Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations. |
|------|--|

Hazardous components which must be listed on the label:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction
Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine
Amines, polyethylenepoly-, tetraethylenepentamine fraction
Amines, polyethylenepoly-, triethylenetetramine fraction

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. EC-No. | Classification | Concentration |
|---------------|-------------------|----------------|---------------|
|---------------|-------------------|----------------|---------------|

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

Version 2.6 Revision Date: 18.10.2024 SDS Number: 400001021218 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.05.2025

| | Index-No. Registration number | | (% w/w) |
|--|----------------------------------|--|----------------------|
| Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction | - - | Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411 | ≥ 50 - < 70 |
| Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine | 68154-62-1 Polymer | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412 | ≥ 30 - < 50 |
| Amines, polyethylenepoly-, tetraethylenepentamine fraction | 90640-66-7 292-587-7 | Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411 | ≥ 5 - < 10 |
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 292-588-2 | Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 | ≥ 0.25 - < 1 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.
Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralise with acid.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

Version 2.6 Revision Date: 18.10.2024 SDS Number: 400001021218 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.05.2025

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : Do not store near acids.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL)

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|--|-----------|-----------------|----------------------------|-------------------|
| Amines, polyethylenepoly-, tetraethylenepentamine fraction | Workers | Inhalation | Long-term systemic effects | 0.82 mg/m3 |
| | Workers | Dermal | Long-term local effects | 0.25 mg/cm2 |
| | Consumers | Inhalation | Long-term systemic effects | 0.14 mg/m3 |
| | Consumers | Dermal | Long-term local effects | 0.021 mg/cm2 |
| | Consumers | Oral | Long-term systemic effects | 0.21 mg/kg bw/day |
| Amines, polyethylenepoly-, triethylenetetramine fraction | Workers | Inhalation | Long-term systemic effects | 0.54 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 0.096 mg/m3 |
| | Consumers | Oral | Long-term systemic effects | 14 mg/kg bw/day |

Predicted No Effect Concentration (PNEC)

| Substance name | Environmental Compartment | Value |
|----------------------------|---------------------------|-----------|
| Amines, polyethylenepoly-, | Fresh water | 0.01 mg/l |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

Version 2.6 Revision Date: 18.10.2024 SDS Number: 400001021218 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.05.2025

| | | |
|--|----------------------------|-------------------------------|
| tetraethylenepentamine fraction | | |
| | Remarks:Assessment Factors | |
| | Marine water | 0.001 mg/l |
| | Remarks:Assessment Factors | |
| | Freshwater - intermittent | 0.068 mg/l |
| | Remarks:Assessment Factors | |
| | Sewage treatment plant | 4.6 mg/l |
| | Remarks:Assessment Factors | |
| | Fresh water sediment | 3.198 mg/kg dry weight (d.w.) |
| | Remarks:Equilibrium method | |
| | Marine sediment | 0.32 mg/kg dry weight (d.w.) |
| | Remarks:Equilibrium method | |
| | Soil | 2.5 mg/kg dry weight (d.w.) |
| | Remarks:Assessment Factors | |
| Amines, polyethylenepoly-, triethylenetetramine fraction | Fresh water | 0.027 mg/l |
| | Marine water | 0.003 mg/l |
| | Sewage treatment plant | 0.13 mg/l |
| | Fresh water sediment | 8.572 mg/kg dry weight (d.w.) |
| | Marine sediment | 0.857 mg/kg dry weight (d.w.) |
| | Soil | 1.25 mg/kg dry weight (d.w.) |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

EN 374 derived from it.

| | | |
|--------------------------|---|--|
| Skin and body protection | : | Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Respiratory protection | : | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 14387 |
| Filter type | : | Combined particulates and ammonia/amines type (K-P) |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | |
|--|---|---|
| Physical state | : | liquid |
| Colour | : | yellow |
| Odour | : | No data is available on the product itself. |
| Odour Threshold | : | No data is available on the product itself. |
| Melting point/freezing point | : | No data is available on the product itself. |
| Boiling point | : | No data is available on the product itself. |
| Flammability (solid, gas) | : | No data is available on the product itself. |
| Lower explosion limit / Lower flammability limit | : | No data is available on the product itself. |
| Upper explosion limit / Upper flammability limit | : | No data is available on the product itself. |
| Flash point | : | > 150 °C Method: Pensky-Martens closed cup |
| Auto-ignition temperature | : | No data is available on the product itself. |
| Decomposition temperature | : | No data is available on the product itself. |
| pH | : | 11 Concentration: 500 g/l |
| Viscosity | : | |
| Viscosity, dynamic | : | 25,000 - 30,000 mPa.s (25 °C) |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Solubility(ies)
Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Density : 0.97 g/cm³ (25 °C)

Relative density : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Acute oral toxicity : LD50 (Rat, male): 3,221 mg/kg
Method: Calculation method
Assessment: The component/mixture is minimally toxic after single ingestion.

Acute dermal toxicity : LD50 (Rabbit, male and female): 1,260 mg/kg
Method: OECD Test Guideline 402

Amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 (Rat, male and female): 1,716.2 mg/kg
Method: OECD Test Guideline 401
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute dermal toxicity : LD50 (Rabbit, male and female): 1,465.4 mg/kg
Method: OECD Test Guideline 402
Assessment: The component/mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Mild skin irritation
GLP : yes

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : human skin
Assessment : May cause eye and skin irritation.
Method : OECD Test Guideline 431

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Result : May cause eye and skin irritation.

Species : human skin
Assessment : Irritant
Method : OECD Test Guideline 439
Result : Irritating to skin.

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Assessment : Irritating to skin.

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Species : reconstructed human epidermis (RhE)
Assessment : Causes burns.
Method : OECD Test Guideline 435
Result : Corrosive after 3 minutes to 1 hour of exposure
GLP : yes

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : reconstructed human epidermis (RhE)
Assessment : Causes burns.
Method : OECD Test Guideline 435
Result : Corrosive after 3 minutes to 1 hour of exposure

Species : Rabbit
Assessment : Causes burns.
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Species : Rabbit
Assessment : Corrosive
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye
GLP : yes

Remarks : May cause irreversible eye damage.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Corrosive

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Assessment : Irritating to eyes.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

| | |
|------------|-----------------------------------|
| Assessment | : Risk of serious damage to eyes. |
| Result | : Risk of serious damage to eyes. |

Amines, polyethylenepoly-, triethylenetetramine fraction:

| | |
|------------|-----------------------------------|
| Species | : Rabbit |
| Assessment | : Risk of serious damage to eyes. |
| Method | : OECD Test Guideline 405 |
| Result | : Irreversible effects on the eye |

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

| | |
|-----------------|--|
| Exposure routes | : Skin |
| Species | : Mouse |
| Method | : OECD Test Guideline 429 |
| Result | : The product is a skin sensitiser, sub-category 1A. |

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

| | |
|------------|--|
| Assessment | : May cause sensitisation by skin contact. |
|------------|--|

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

| | |
|------------|--|
| Assessment | : May cause sensitisation by skin contact. |
| Result | : May cause sensitisation by skin contact. |

Amines, polyethylenepoly-, triethylenetetramine fraction:

| | |
|-----------------|---|
| Exposure routes | : Skin |
| Species | : Guinea pig |
| Assessment | : Probability or evidence of skin sensitisation in humans |
| Method | : OECD Test Guideline 406 |
| Result | : Probability or evidence of skin sensitisation in humans |

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

| | |
|-----------------------|---|
| Genotoxicity in vitro | : Metabolic activation: with and without metabolic activation |
| | Method: OECD Test Guideline 471 |
| | Result: negative |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 487
Result: negative

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Genotoxicity in vitro : Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Test Type: sister chromatid exchange assay
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: positive

Test Type: gene mutation test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Test Type: Micronucleus test
Test system: Human lymphocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 487
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (male and female)
Cell type: Bone marrow
Application Route: Intraperitoneal injection
Dose: 185/370/600 mg/kg
Method: OECD Test Guideline 474
Result: negative
Remarks: Information given is based on data obtained from similar substances.

Amines, polyethylenepoly-, triethylenetetramine fraction:

Genotoxicity in vitro : Test Type: reverse mutation assay
Test system: Salmonella tryphimurium and E. coli
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive
GLP: yes

Test Type: Micronucleus test
Test system: Human lymphocytes
Metabolic activation: with and without metabolic activation

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Method: OECD Test Guideline 487

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (male and female)
Cell type: Bone marrow
Application Route: Intraperitoneal injection
Dose: 0 - 600 mg/kg
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Mouse, male
Application Route : Dermal
NOAEL : ≥ 50 mg/kg bw/day
Method : OECD Test Guideline 451
Result : negative

Species : Mouse, male
Application Route : Dermal
Exposure time : 104 weeks
NOAEL : ≥ 20 mg/kg bw/day
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 422
Result: Animal testing did not show any effects on fertility.

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Effects on foetal development : Test Type: Pre-natal
Species: Rabbit, female
Application Route: Dermal
Dose: 5/50/125 mg/kg bw/d
Duration of Single Treatment: 13 d
General Toxicity Maternal: NOAEL: 50 mg/kg body weight
Developmental Toxicity: NOAEL: ≥ 125 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects
Remarks: Information given is based on data obtained from similar substances.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 75/325/750 mg/kg bw/d
Duration of Single Treatment: 10 d
General Toxicity Maternal: NOAEL: \geq 750 mg/kg body weight
Developmental Toxicity: NOAEL: \geq 750 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects
Remarks: Information given is based on data obtained from similar substances.

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 200/400/800 mg/kg bw/d
Duration of Single Treatment: 14 d
General Toxicity Maternal: NOEL: 200 mg/kg body weight
Developmental Toxicity: NOAEL: \geq 400 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects
Remarks: Information given is based on data obtained from similar substances.

Amines, polyethylenepoly-, triethylenetetramine fraction:

Effects on foetal development : Test Type: Pre-natal
Species: Rat
Application Route: Oral
Dose: 75/325/750 mg/kg bw/day
Duration of Single Treatment: 10 d
General Toxicity Maternal: NOAEL: \geq 750 mg/kg body weight
Developmental Toxicity: NOAEL: \geq 750 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit
Application Route: Dermal
Dose: 5/50/125 mg/kg bw/day
Duration of Single Treatment: 13 d
General Toxicity Maternal: NOAEL: 50 mg/kg body weight
Developmental Toxicity: NOAEL: \geq 125 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Repeated dose toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

| | |
|---------------------|------------------------|
| Species | : Rat, male and female |
| NOAEL | : 1000 mg/kg |
| Application Route | : Ingestion |
| Exposure time | : 6 Weeks |
| Number of exposures | : 7 d |
| Method | : Subacute toxicity |

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

| | |
|-------------------|--|
| Species | : Rat, male and female |
| NOAEL | : 350 mg/kg/d |
| Application Route | : Oral |
| Exposure time | : 28 d |
| Dose | : 100/350/1200 mg/kg bw/day |
| Method | : OECD Test Guideline 407 |
| Target Organs | : Lungs |
| Remarks | : Information given is based on data obtained from similar substances. |

| | |
|-------------------|--|
| Species | : Rat, female |
| NOAEL | : 50 mg/kg |
| Application Route | : Oral |
| Exposure time | : 90 d |
| Dose | : 50/175/600 mg/kg bw/d |
| Method | : OECD Test Guideline 408 |
| Target Organs | : Lungs |
| Remarks | : Information given is based on data obtained from similar substances. |

| | |
|-------------------|--|
| Species | : Dog, male and female |
| NOAEL | : 125 mg/kg |
| Application Route | : Oral |
| Exposure time | : 28 d |
| Target Organs | : Lungs |
| Remarks | : Information given is based on data obtained from similar substances. |

| | |
|---------------------|--|
| Species | : Rat, male and female |
| NOAEL | : 350 mg/kg |
| Application Route | : Oral |
| Exposure time | : 4 weeks |
| Number of exposures | : daily |
| Dose | : 100/350/1200 mg/kg bw/d |
| Method | : OECD Test Guideline 408 |
| Remarks | : Information given is based on data obtained from similar substances. |

| | |
|-------------------|-------------------------|
| Species | : Rat, male and female |
| NOAEL | : 600 - 3000 ppm |
| Application Route | : oral (drinking water) |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Exposure time : 92 days
Dose : 120/600/3000 ppm
Method : OECD Test Guideline 408
Remarks : Information given is based on data obtained from similar substances.

Species : Mouse, male and female
NOAEL : 600 ppm
Application Route : oral (drinking water)
Exposure time : 92 days
Dose : 120/600/3000 ppm
Method : OECD Test Guideline 408
Remarks : Information given is based on data obtained from similar substances.

Species : Rabbit, male and female
NOEL : >= 200 mg/kg
Application Route : Dermal
Exposure time : 20 days 6 h
Number of exposures : 5 days/week
Dose : 50/100/200 mg/kg bw/day
Method : OECD Test Guideline 410

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rat, male and female
NOAEL : 350 mg/kg
Application Route : Oral
Exposure time : 28 d
Number of exposures : 7 d
Dose : 100/350/1000 mg/kg bw/day
Method : OECD Test Guideline 407
Target Organs : Lungs
Remarks : Information given is based on data obtained from similar substances.

Species : Dog, male and female
NOAEL : 125 mg/kg
Application Route : Oral
Target Organs : Lungs
Remarks : Information given is based on data obtained from similar substances.

Species : Dog, male and female
NOAEL : 50 mg/kg
Application Route : Oral
Method : Subchronic toxicity
Remarks : Information given is based on data obtained from similar substances.

Species : Rat, male and female
NOAEL : 50 mg/kg
Application Route : Oral
Exposure time : 26 weeks
Dose : 50/175/600 mg/kg bw/day

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Method : OECD Test Guideline 408
Target Organs : Lungs
Remarks : Information given is based on data obtained from similar substances.

Species : Mouse, male and female
NOAEL : 92 mg/kg, 600 ppm
Application Route : Oral
Exposure time : 120/600/3000 ppm
Method : OECD Test Guideline 408
Remarks : Information given is based on data obtained from similar substances.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 7.07 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 5.18 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2.43 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): 421 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 420 mg/l
End point: mortality
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.1.
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 24.1 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: Tested according to Annex V of Directive 67/548/EEC.

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 6.8 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 0.5 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 97.3 mg/l
Exposure time: 2 h
Test Type: static test
Test substance: Fresh water

NOEC : 500 mg/l
Exposure time: 28 d

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Method: OECD Test Guideline 216

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 1.9 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Fresh water
Method: OECD Test Guideline 202
Remarks: Information given is based on data obtained from similar substances.

Toxicity to soil dwelling organisms : NOEC: 125 mg/kg
Exposure time: 55 d
Species: Eisenia fetida (earthworms)
Method: OECD Test Guideline 222

Amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 570 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.1.

LC50 (Leuciscus idus (Golden orfe)): 200 - 500 mg/l
Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 330 mg/l
End point: mortality
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: EPA OTS 797.1400

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 31.1 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l
Exposure time: 72 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 201

EC10 (Selenastrum capricornutum (green algae)): 1.34 mg/l
Exposure time: 72 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Bacteria): \geq 100 mg/l
Exposure time: 28 d
Method: OECD Test Guideline 216

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

EC50 (Bacteria): > 100 mg/l
Exposure time: 28 h
Method: OECD Test Guideline 216

EC50 (Bacteria): 15.7 mg/l
Exposure time: 2 h
Test Type: static test
Test substance: Fresh water

NOEC (Bacteria): 1.3 mg/l
Exposure time: 2 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other : EC10: 1.9 mg/l
aquatic invertebrates
(Chronic toxicity) Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to soil dwelling : NOEC: ca. 62.5 mg/kg
organisms Exposure time: 56 d
Species: Eisenia fetida (earthworms)
Method: OECD Test Guideline 222

EC50: > 1,000 mg/kg
Exposure time: 56 d
Species: Eisenia fetida (earthworms)
Method: OECD Test Guideline 222

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not inherently biodegradable.
Biodegradation: 17 %
Exposure time: 84 d
Method: OECD Test Guideline 302 A
Test substance: Fresh water

Test Type: aerobic
Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 162 d
Method: OECD Test Guideline 301D
Test substance: Fresh water

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Amines, polyethylenepoly-, triethylenetetramine fraction:

Biodegradability : Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 162 d
Method: OECD Test Guideline 301D
Test substance: Fresh water

Test Type: aerobic
Inoculum: activated sludge
Result: Not inherently biodegradable.
Biodegradation: 20 %
Related to: Dissolved organic carbon (DOC)
Exposure time: 84 d
Method: OECD Test Guideline 302A
Test substance: Fresh water

12.3 Bioaccumulative potential

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Partition coefficient: n-octanol/water : log Pow: -2.6 (20 °C)

Amines, polyethylenepoly-, triethylenetetramine fraction:

Partition coefficient: n-octanol/water : log Pow: -2.08 - 2.90 (20 °C)
Method: QSAR

12.4 Mobility in soil

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Distribution among environmental compartments : Koc: 3.2 - 3.7
Method: OECD Test Guideline 106

Amines, polyethylenepoly-, triethylenetetramine fraction:

Distribution among environmental compartments : Koc: 3162.28, log Koc: 3.5
Method: OECD Test Guideline 106

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

| | | |
|-----------------------------------|---|--|
| Endocrine disrupting potential | : | This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f). |
| Additional ecological information | : | An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects. |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

| | | |
|------------------------|---|---|
| Product | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. |
| Contaminated packaging | : | Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. |

SECTION 14: Transport information

14.1 UN number or ID number

| | | |
|------|---|---------|
| ADR | : | UN 3082 |
| RID | : | UN 3082 |
| IMDG | : | UN 3082 |
| IATA | : | UN 3082 |

14.2 UN proper shipping name

| | | |
|------|---|--|
| ADR | : | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POLYAMIDE RESIN) |
| RID | : | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POLYAMIDE RESIN) |
| IMDG | : | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POLYAMIDE RESIN) |
| IATA | : | Environmentally hazardous substance, liquid, n.o.s. (POLYAMIDE RESIN) |

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|-----|-------|------------------|
| ADR | : | 9 |
| RID | : | 9 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

IMDG : 9

IATA : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

| | |
|---|---|
| UK REACH List of restrictions (Annex 17) | : Conditions of restriction for the following entries should be considered: Number on list 3 |
| UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation | : This product does not contain substances of very high concern. |
| UK REACH List of substances subject to authorisation (Annex XIV) | : Not applicable |

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

| | |
|-------|--|
| DSL | : All components of this product are on the Canadian DSL |
| AIIC | : On the inventory, or in compliance with the inventory |
| ENCS | : On the inventory, or in compliance with the inventory |
| KECI | : On the inventory, or in compliance with the inventory |
| PICCS | : Not in compliance with the inventory |
| IECSC | : On the inventory, or in compliance with the inventory |
| TCSI | : On the inventory, or in compliance with the inventory |
| TSCA | : All substances listed as active on the TSCA inventory |

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

| | |
|------|--|
| H302 | : Harmful if swallowed. |
| H312 | : Harmful in contact with skin. |
| H314 | : Causes severe skin burns and eye damage. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| H412 | : Harmful to aquatic life with long lasting effects. |

Full text of other abbreviations

| | |
|-----------------|--------------------------------------|
| Acute Tox. | : Acute toxicity |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Eye Dam. | : Serious eye damage |
| Eye Irrit. | : Eye irritation |
| Skin Corr. | : Skin corrosion |
| Skin Irrit. | : Skin irritation |
| Skin Sens. | : Skin sensitisation |

Further information

Classification of the mixture:

| | |
|-------------------|------|
| Eye Dam. 1 | H318 |
| Skin Sens. 1 | H317 |
| Aquatic Chronic 2 | H411 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA HARDENER

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 2.6 | 18.10.2024 | 400001021218 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® STANDARD ULTRA RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy constituents

1.3 Details of the supplier of the safety data sheet

Company : HUNTSMAN ADVANCED MATERIALS (UK) LIMITED
Address : Ickleton Road, Duxford, Cambridgeshire
CB22 4XQ United Kingdom
Telephone : +41 61 299 20 41
E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

| | |
|--|--|
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Long-term (chronic) aquatic hazard, Category 2 | H411: Toxic to aquatic life with long lasting effects. |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms



Signal word

: Warning

Hazard statements

| | |
|------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

| | |
|------|---|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read carefully and follow all instructions. |

Prevention:

| | |
|------|--|
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/ eye protection/ face protection. |

Response:

| | |
|------|-------------------|
| P391 | Collect spillage. |
|------|-------------------|

Disposal:

| | |
|------|--|
| P501 | Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations. |
|------|--|

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxy)phenyl]propane
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane
bisphenol A - epoxy resins, number average MW >700 - <1100

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. | Classification | Concent |
|---------------|---------|----------------|---------|
|---------------|---------|----------------|---------|

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.6 Revision Date: 18.09.2024 SDS Number: 400001021217 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.05.2025

| | EC-No. Index-No. Registration number | | ration (% w/w) |
|---|--|---|-------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 216-823-5 603-073-00-2 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 ≥ 5 % Skin Irrit. 2; H315 ≥ 5 % | ≥ 70 - < 90 |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane | - - | Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411 | ≥ 2.5 - < 10 |
| bisphenol A - epoxy resins, number average MW >700 - <1100 | 25068-38-6 Polymer | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 | ≥ 1 - < 10 |
| Substances with a workplace exposure limit : | | | |
| Silica, amorphous, fumed, cryst.-free | 112945-52-5 - | | ≥ 1 - < 10 |

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- If inhaled : If inhaled, remove to fresh air.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Get medical attention if symptoms occur.

- | | | |
|-------------------------|---|--|
| In case of skin contact | : | If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes. |
| In case of eye contact | : | Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|-------|---|---|
| Risks | : | Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. |
|-------|---|---|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : | Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical |
| Unsuitable extinguishing media | : | Exercise caution when using a high volume water jet as it may scatter and spread fire |

5.2 Special hazards arising from the substance or mixture

- | | | |
|--------------------------------------|---|---|
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | Carbon oxides Phenolics |

5.3 Advice for firefighters

- | | | |
|---|---|---|
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : | Collect contaminated fire extinguishing water separately. This |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.6 Revision Date: 18.09.2024 SDS Number: 400001021217 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.05.2025

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------------------------|-------------|-------------------------------|--------------------------------|---------|
| Silica, amorphous, fumed, cryst.-free | 112945-52-5 | TWA (inhalable dust) | 6 mg/m ³ (Silica) | GB EH40 |
| | | TWA (Respirable dust) | 2.4 mg/m ³ (Silica) | GB EH40 |

Derived No Effect Level (DNEL)

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|--|-----------|-----------------|----------------------------|-------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]p ropane | Workers | Inhalation | Long-term systemic effects | 4.93 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 0.75 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 0.87 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 0.0893 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 0.5 mg/kg bw/day |
| bisphenol A - epoxy resins, number average MW >700 - <1100 | Workers | Dermal | Systemic effects | |
| | Workers | Inhalation | Systemic effects | 12.25 mg/m ³ |
| | Workers | Dermal | Systemic effects | |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.6 Revision Date: 18.09.2024 SDS Number: 400001021217 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.05.2025

| | | | | |
|---|-----------|------------|---------------------------------------|--------------------|
| | Workers | Inhalation | Systemic effects | 12.25 mg/m3 |
| | Consumers | Dermal | Systemic effects | |
| | Consumers | Oral | Systemic effects | |
| | Consumers | Dermal | Systemic effects | |
| | Consumers | Oral | Systemic effects | |
| bis(2-ethylhexyl) adipate | Workers | Inhalation | Long-term systemic effects | 17.8 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 25.5 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 4.4 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 13 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 1.7 mg/kg bw/day |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane | Workers | Dermal | Acute local effects | 0.0083 mg/cm2 |
| | Workers | Dermal | Long-term systemic effects | 104.15 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 29.39 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 62.5 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 8.7 mg/m3 |
| | Consumers | Oral | Long-term systemic effects | 6.25 mg/kg bw/day |
| Silica, amorphous, fumed, cryst.-free | Workers | Inhalation | Long-term systemic effects | 4 mg/m3 |
| reaction product: bisphenol a-(epichlorhydrin); epoxy resin (number average molecular weight > 1100) | Workers | Dermal | Systemic effects, Short-term exposure | 8.33 mg/kg bw/day |
| | Workers | Inhalation | Systemic effects, Short-term exposure | 12.25 mg/m3 |
| | Workers | Dermal | Systemic effects, Long-term exposure | 8.33 mg/kg bw/day |
| | Workers | Inhalation | Systemic effects, Long-term exposure | 12.25 mg/m3 |
| | Consumers | Dermal | Systemic effects, Short-term exposure | 3.571 mg/kg bw/day |
| | Consumers | Oral | Systemic effects, | 0.75 mg/kg |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.6 Revision Date: 18.09.2024 SDS Number: 400001021217 Date of last issue: 13.12.2023
Date of first issue: 20.07.2018

Print Date 10.05.2025

| | | | | |
|--|-----------|--------|---|-----------------------|
| | | | Short-term exposure | bw/day |
| | Consumers | Dermal | Systemic effects, Long-term exposure | 3.571 mg/kg bw/day |
| | Consumers | Oral | Systemic effects, Long-term exposure | 0.75 mg/kg bw/day |

Predicted No Effect Concentration (PNEC)

| Substance name | Environmental Compartment | Value |
|----------------|----------------------------|--------------|
| 25068-38-6 | Fresh water | 0.006 mg/l |
| | Remarks:Assessment Factors | |
| | Marine water | 0.0006 mg/l |
| | Remarks:Assessment Factors | |
| | Freshwater - intermittent | 0.018 mg/l |
| | Remarks:Assessment Factors | |
| | Fresh water sediment | 0.996 mg/kg |
| | Remarks:Equilibrium method | |
| | Marine sediment | 0.0996 mg/kg |
| | Remarks:Equilibrium method | |
| | Soil | 0.196 mg/kg |
| | Remarks:Equilibrium method | |
| | Sewage treatment plant | 10 mg/l |
| | Remarks:Assessment Factors | |
| | Secondary Poisoning | 11 mg/kg |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Neoprene gloves

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | : liquid |
| Colour | : light cream |
| Odour | : slight |
| Odour Threshold | : No data is available on the product itself. |
| Melting point/freezing point | : No data is available on the product itself. |
| Boiling point | : No data is available on the product itself. |
| Flammability (solid, gas) | : No data is available on the product itself. |
| Lower explosion limit / Lower flammability limit | : No data is available on the product itself. |
| Upper explosion limit / Upper flammability limit | : No data is available on the product itself. |
| Flash point | : 210 °C Method: Pensky-Martens closed cup |
| Auto-ignition temperature | : No data is available on the product itself. |
| Decomposition temperature | : No data is available on the product itself. |
| pH | : 6 Concentration: 500 g/l |
| Viscosity | : No data is available on the product itself. |
| Solubility(ies) | |
| Water solubility | : practically insoluble |
| Solubility in other solvents | : No data is available on the product itself. |
| Partition coefficient: n-octanol/water | : No data is available on the product itself. |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

| | |
|--------------------------|---|
| Vapour pressure | : 0.0001 kPa |
| Density | : 1.15 g/cm ³ (25 °C) |
| Relative density | : No data is available on the product itself. |
| Relative vapour density | : No data is available on the product itself. |
| Particle characteristics | : No data is available on the product itself. |

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Silica, amorphous, fumed, cryst.-free:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): > 58.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Species : Rabbit
Exposure time : 4 h
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

| | |
|---------|---------------------------|
| Species | : Rabbit |
| Method | : OECD Test Guideline 404 |
| Result | : Irritating to skin. |

bisphenol A - epoxy resins, number average MW >700 - <1100:

| | |
|--------|---------------------------|
| Method | : OECD Test Guideline 404 |
| Result | : Skin irritation |

Silica, amorphous, fumed, cryst.-free:

| | |
|------------|---------------------------|
| Species | : Rabbit |
| Assessment | : No skin irritation |
| Method | : OECD Test Guideline 404 |
| Result | : No skin irritation |

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

| | |
|------------|---------------------------|
| Species | : Rabbit |
| Assessment | : Irritating to eyes. |
| Method | : OECD Test Guideline 405 |
| Result | : Irritating to eyes. |

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

| | |
|---------|---------------------------|
| Species | : Rabbit |
| Method | : OECD Test Guideline 405 |
| Result | : No eye irritation |

bisphenol A - epoxy resins, number average MW >700 - <1100:

| | |
|---------|---------------------------|
| Species | : Rabbit |
| Method | : OECD Test Guideline 405 |
| Result | : Eye irritation |

Silica, amorphous, fumed, cryst.-free:

| | |
|------------|---------------------------|
| Species | : Rabbit |
| Assessment | : No eye irritation |
| Method | : OECD Test Guideline 405 |
| Result | : No eye irritation |

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Respiratory sensitisation

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

| | |
|-----------------|--|
| Test Type | : Local lymph node assay (LLNA) |
| Exposure routes | : Skin |
| Species | : Mouse |
| Method | : OECD Test Guideline 429 |
| Result | : The product is a skin sensitiser, sub-category 1B. |

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

| | |
|-----------------|--|
| Test Type | : Local lymph node assay (LLNA) |
| Exposure routes | : Skin |
| Species | : Mouse |
| Method | : OECD Test Guideline 429 |
| Result | : The product is a skin sensitiser, sub-category 1A. |

bisphenol A - epoxy resins, number average MW >700 - <1100:

| | |
|-----------------|--|
| Exposure routes | : Skin |
| Species | : Guinea pig |
| Method | : OECD Test Guideline 406 |
| Result | : May cause sensitisation by skin contact. |

Germ cell mutagenicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

| | |
|-----------------------|---|
| Genotoxicity in vitro | : Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: without metabolic activation Result: positive Test Type: reverse mutation assay Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay) Result: negative |
| Genotoxicity in vivo | : Test Type: in vivo assay Species: Mouse (male) Cell type: Germ Application Route: Oral Dose: 3333, 10000 mg/kg Result: negative Test Type: gene mutation test Species: Rat (male) |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Cell type: Somatic
Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Genotoxicity in vivo : Cell type: Somatic
Application Route: Oral
Exposure time: 48 h
Dose: 2000 mg/kg
Method: OECD Test Guideline 474
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 2000 mg/kg
Method: OECD Test Guideline 486
Result: negative

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: Positive results were obtained in some in vitro tests.

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Silica, amorphous, fumed, cryst.-free:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Application Route: Inhalation
Dose: 50 mg/m³
Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Species : Rat, male
Application Route : Oral
Exposure time : 24 month(s)
Dose : 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment : 7 days/week
NOAEL : 15 mg/kg bw/day
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)
Dose : 0, 0.1, 10, 100 mg/kg bw/day
Frequency of Treatment : 3 days/week
NOEL : 0.1 mg/kg body weight
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)
Dose : 0.1, 100, 1000 mg/kg bw/day
Frequency of Treatment : 5 days/week
NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453
Result : negative

Species : Rat, female
Application Route : Oral
Exposure time : 24 month(s)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Dose : 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment : 7 days/week
NOAEL : 100 mg/kg bw/day
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

Species : Rat, females
Application Route : Oral
Exposure time : 24 month(s)
Dose : 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment : 7 days/week
NOEL : 2 mg/kg bw/day
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species : Rat, male and female
Application Route : Oral
Exposure time : 24 month(s)
Dose : 15 mg/kg
Frequency of Treatment : 7 daily
Method : OECD Test Guideline 453
Result : negative

Silica, amorphous, fumed, cryst.-free:

Species : Rat, male and female
Application Route : Oral
Exposure time : 103 weeks
Dose : 1800 - 3200 mg/kg
Frequency of Treatment : 7 daily
Method : OECD Test Guideline 453
Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 milligram per kilogram
Duration of Single Treatment: 238 d
Frequency of Treatment: 1 daily
General Toxicity - Parent: NOEL: 540 mg/kg body weight
General Toxicity F1: NOEL: 750 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
Dose: 0, 30, 100 or 300 milligram per kilogram
Duration of Single Treatment: 28 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Developmental Toxicity: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Developmental Toxicity: NOAEL: > 540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 mg/kg/
Duration of Single Treatment: 238 d
General Toxicity - Parent: NOEL: 750
General Toxicity F1: NOEL: 750 mg/kg body weight
General Toxicity F2: NOAEL: 750 mg/kg body weight
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
General Toxicity - Parent: NOEL: 750 mg/kg body weight

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

General Toxicity F1: NOEL: 750 mg/kg body weight
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Effects on foetal development

: Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Silica, amorphous, fumed, cryst.-free:

Effects on foetal development

: Species: Mouse
Application Route: Oral
General Toxicity Maternal: NOAEL: 1,340 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rabbit
Application Route: Oral
General Toxicity Maternal: NOAEL: 1,600 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat
Application Route: Oral
General Toxicity Maternal: NOAEL: 1,350 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Species : Rat, male and female
NOAEL : 50 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Application Route : oral (gavage)
Exposure time : 14 Weeks
Number of exposures : 7 d
Dose : 0, 50, 250, 1000 mg/kg/day
Method : OECD Test Guideline 408

Species : Rat, male and female
NOAEL : ≥ 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 5 d
Dose : 0, 10, 100, 1000 mg/kg/day
Method : OECD Test Guideline 411

Species : Mouse, male
NOAEL : 100 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 3 d
Dose : 0, 1, 10, 100 mg/kg/day
Method : OECD Test Guideline 411

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Species : Rat, male and female
NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Number of exposures : 7 d
Method : Subchronic toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species : Rat, male and female
NOAEL : 50 mg/kg
Application Route : Ingestion
Exposure time : 14 Weeks
Number of exposures : 7 d
Method : Subchronic toxicity

Species : Rat, male and female
NOEL : 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 5 d
Method : Subchronic toxicity

Silica, amorphous, fumed, cryst.-free:

Species : Rat, male and female
NOAEL : 7950 - 8980 mg/kg
Application Route : Ingestion
Exposure time : 4,320 h
Number of exposures : 7 d

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

| | | |
|---------------------|---|-------------------------|
| Method | : | Subchronic toxicity |
| Species | : | Rat, male and female |
| NOEC | : | 4000 - 4500 mg/m3 |
| Application Route | : | Ingestion |
| Test atmosphere | : | dust/mist |
| Exposure time | : | 13 Weeks |
| Number of exposures | : | 7 d |
| Method | : | OECD Test Guideline 413 |

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 : 11 mg/l
plants
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

NOEC : 4.2 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Toxicity to fish : LC50 (Fish): 2.54 mg/l
Exposure time: 96 h
Test substance: Fresh water
Method: Calculation method

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.55 mg/l
Exposure time: 48 h
Method: Calculation method

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): > 1.8 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: no

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
GLP: no

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Analytical monitoring: no

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Test substance: Fresh water
Method: OECD Test Guideline 211
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EgC50 (Selenastrum capricornutum (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Silica, amorphous, fumed, cryst.-free:

Toxicity to fish : LL50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): >= 1,000 mg/l
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

12.2 Persistence and degradability

Components:

bis-[4-(2,3-epoxypropoxy)phenyl]propane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Concentration: 3 mg/l
Result: Not biodegradable
Biodegradation: ca. 0 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.E.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability : Test Type: aerobic
Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not biodegradable
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

12.3 Bioaccumulative potential

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3.242 (25 °C)
pH: 7.1
Method: OECD Test Guideline 117

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 150
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 2.7 - 3.6
Method: OECD Test Guideline 117
GLP: yes

bisphenol A - epoxy resins, number average MW >700 - <1100:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

12.4 Mobility in soil

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Distribution among environmental compartments : Koc: 445

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Distribution among environmental compartments : Koc: 4460
Method: OECD Test Guideline 121

bisphenol A - epoxy resins, number average MW >700 - <1100:

Distribution among environmental compartments : Koc: 445

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local, regional, national and international regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|-------------|-------|------------------|
| ADR | : 9 | |
| RID | : 9 | |
| IMDG | : 9 | |
| IATA | : 9 | |

14.4 Packing group

| | |
|--|-----------------|
| ADR | |
| Packing group | : III |
| Classification Code | : M6 |
| Hazard Identification Number | : 90 |
| Labels | : 9 |
| Tunnel restriction code | : (-) |
| RID | |
| Packing group | : III |
| Classification Code | : M6 |
| Hazard Identification Number | : 90 |
| Labels | : 9 |
| IMDG | |
| Packing group | : III |
| Labels | : 9 |
| EmS Code | : F-A, S-F |
| IATA (Cargo) | |
| Packing instruction (cargo aircraft) | : 964 |
| Packing instruction (LQ) | : Y964 |
| Packing group | : III |
| Labels | : Miscellaneous |
| IATA (Passenger) | |
| Packing instruction (passenger aircraft) | : 964 |
| Packing instruction (LQ) | : Y964 |
| Packing group | : III |
| Labels | : Miscellaneous |

14.5 Environmental hazards

| | |
|---------------------------|-------|
| ADR | |
| Environmentally hazardous | : yes |
| RID | |
| Environmentally hazardous | : yes |
| IMDG | |
| Marine pollutant | : yes |
| IATA (Passenger) | |
| Environmentally hazardous | : yes |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

| | | |
|---|---|---|
| UK REACH List of restrictions (Annex 17) | : | Conditions of restriction for the following entries should be considered: Number on list 3 |
| UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation | : | This product does not contain substances of very high concern. |
| UK REACH List of substances subject to authorisation (Annex XIV) | : | Not applicable |

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

| | | |
|-------|---|--|
| DSL | : | All components of this product are on the Canadian DSL |
| AIIC | : | On the inventory, or in compliance with the inventory |
| ENCS | : | On the inventory, or in compliance with the inventory |
| KECI | : | On the inventory, or in compliance with the inventory |
| PICCS | : | On the inventory, or in compliance with the inventory |
| IECSC | : | On the inventory, or in compliance with the inventory |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

| | |
|------|--|
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H319 | : Causes serious eye irritation. |
| H411 | : Toxic to aquatic life with long lasting effects. |

Full text of other abbreviations

| | |
|-----------------|--|
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Eye Irrit. | : Eye irritation |
| Skin Irrit. | : Skin irritation |
| Skin Sens. | : Skin sensitisation |
| GB EH40 | : UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 / TWA | : Long-term exposure limit (8-hour TWA reference period) |

Further information

Classification of the mixture:

| | |
|-------------------|------|
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| Skin Sens. 1 | H317 |
| Aquatic Chronic 2 | H411 |

Classification procedure:

| |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 13.12.2023 |
| 1.6 | 18.09.2024 | 400001021217 | Date of first issue: 20.07.2018 |

Print Date 10.05.2025

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.