Milliput Component A Page 1 of 7

SAFETY DATA SHEET

Revision: 2 May 2022 Version number: 1.0

SECTION 1: Identification of the substance/mixture and company/undertaking

1.1 Product identifier Milliput Component A

Colour variations: Standard, Teracotta, Black, Superfine White, Silver

Grey, and Turquoise-Blue.

1.2 Relevant identified uses Component A of two-part, cold-setting epoxy putty.

of the substance or mixture and uses

Uses advised against: not available.

advised against

1.3 Details of the supplier of the safety data sheet

The Milliput Company, Unit 8, The Marian,

Dolgellau,

Gwynedd LL40 1UU, UK.

Tel 01341 422562; info@milliput.co.uk.

1.4 Emergency telephone

number

Tel 01341 422562 (UK business hours).

UK: 111 (public NHS number for less urgent medical problems). Medical professionals can contact the National Poisons Information Service

(NPIS): 0344 892 0111.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to CLP Regulation: UK SI 2019 No. 720 and EU Regulation 1272/2008.

Skin Irrit 2, H315; Eye Irrit 2, H319; Skin Sens 1, H317; Aquatic Chronic 2, H411.

See Section 16 'Other information' for full text of the H-statements.

2.2 Label elements





Signal word Warning

Hazard statements Causes skin irritation.

Causes serious eye irritation. May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

Precautionary statements

general Keep out of reach of children.

prevention Wear protective gloves and eye protection.

response If skin irritation or rash occurs: Get medical attention.

If eye irritation persists: Get medical attention.

storage None.

Milliput Component A Page 2 of 7

SAFETY DATA SHEET

Revision: 2 May 2022 Version number: 1.0

disposal Dispose of contents/container in accordance with local/national

regulation.

Supplemental information

None.

2.3 Other hazards Not available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures a,b

Declarable components	Conc. (wt%)	EC No.	CAS No.	REACH Reg. No.	Classification, supplemental hazards, ATE, M-factor, and SCL
Epoxy resin ^c	25–50	500-033-5	25068-38- 6	NA	Skin Irrit 2, H315; Eye Irrit 2, H319; Skin Sens 1, H317; Aquatic Chronic 2, H411
Other components					
Not available					

a NA: not available.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation If inhalation of product is suspected of causing symptoms, remove

exposed person to fresh air and keep at rest in a position comfortable for breathing. For difficulties in breathing, respiratory irritation, or other

symptoms, get medical attention.

Skin For signs of irritation or rash, wash affected area with soap and water. Get

medical attention if irritation or rash persists.

Eye If in eye, rinse with room-temperature water or eyewash solution for

several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if irritation persists.

Ingestion If in mouth, rinse out with water. Give water to drink if the product has

been swallowed. Get medical attention if exposed person feels unwell. Do

not induce vomiting, unless instructed by medical personnel.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation and may cause an allergic skin reaction. Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptoms as they occur.

^b See Section 16 'Other information' for full text of the H-statements.

^c Chemical name: 4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane.

Milliput Component A Page 3 of 7

SAFETY DATA SHEET

Revision: 2 May 2022 Version number: 1.0

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable Water spray, alcohol-resistant foam, carbon dioxide, or dry powder.

Unsuitable Water jet may spread fire.

5.2 Special hazards arising from the substance or mixture

The product is not classified as flammable. If involved in a fire, product will decompose producing hazardous smoke, vapours and gases.

e substance or will decompose producing nazardous smoke, vapours and gases.

5.3 Advice for firefighters Remove product from should wear self-cor

Remove product from fire or cool containers with water spray. Firefighters should wear self-contained breathing apparatus and full protective

clothing.

Prevent water from firefighting from entering water-courses or drainage

system.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Product is supplied in small packages for consumers which can be

collected.

For large spills in a a professional setting, wear personal protection.

Follow prescribed procedures for responding to workplace spills.

6.2 Environmental precautions

Prevent product from entering water courses or drainage system.

6.3 Methods and material for containment and cleaning up

Clean up spill as soon as possible.

For small quantities, collect product or wipe off residue with cloth or paper.

For larger quantities, absorb onto an inert material (eg sand), and sweep

up.

Rinse contaminated surfaces with soap and water. Collect waste,

washings, and contaminated materials for safe disposal.

6.4 Reference to other

sections

For recommended personal protective equipment, see Section 8.

For disposal considerations, see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

See Section 8 for engineering controls and personal protection.

Keep out of reach of children.

For bulk handling, avoid skin and eye contact with the product, using measures described in Section 8. Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities

For bulk storage, keep container closed. Store containers in a cool, dry place away from direct sunlight.

7.3 Specific end use(s) Component A of two-part, cold-setting epoxy putty.

Milliput Component A Page 4 of 7

SAFETY DATA SHEET

Revision: 2 May 2022 Version number: 1.0

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

EU limit values None.

National limit values (UK) Talc, respirable dust: WEL: 8 h TWA, 1 mg/m³.

Monitoring procedure Not available. Other: human Not available.

(DNELs, DMELs)

Other: environmental

Not available.

(PNEC)

8.2 Exposure controls

Engineering controls For workplace use, good general ventilation (eg 3-5 air exchanges per

hour) is recommended.

Personal protective For handling in the workplace, the need for personal protective equipment equipment

should be based on a risk assessment for the particular use.

Avoid skin contact by wearing chemical resistant gloves (eg nitrile, 0.2 mm) and safety goggles. If extensive contact may occur, wear protective

clothing (eg apron, lab coat).

Respiratory protective equipment not required for foreseen use.

PPE should conform to GB or European (EN) standards. Consult

manufacturer concerning breakthrough times.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

(a) Physical state Liquid (paste)

(b) Colour Various colours (Standard, Teracotta, Black, Superfine White, Silver

Grey, and Turquoise-Blue)

(c) Odour Characteristic

(d) Melting/freezing point Not available; epoxy resin -16 °C

(e) Boiling point or initial boiling point and boiling

range

Not available; epoxy resin 320 °C

(f) Flammability Not available

upper (g) Lower

explosion limit

Not available

Not available; epoxy resin 266 °C (h) Flash point

(i) Auto-ignition temp. Not available Not available Decomposition temp. (k) pH Not available Milliput Component A Page 5 of 7

SAFETY DATA SHEET

Revision: 2 May 2022 Version number: 1.0

(I) Kinematic viscosity Not available

(m) Solubility Water: epoxy resin 7 mg/L at 25 °C

(n) Partition coeff. noctanol/water (log value) Epoxy resin 3.2 at 25 °C (calculated)

(o) Vapour pressure Not available; epoxy resin < 0.001 Pa at 20 °C (estimate)

(p) Density or rel. density Not available
(q) Relative vapour density Not available
(r) Particle characteristics Not available

9.2 Other information Not considered explosive or oxidising

SECTION 10: Stability and reactivity

10.1 Reactivity Not available.

10.2 Chemical stability Stable under recommended storage and handling conditions. No

hazardous polymerization.

10.3 Possibility of

hazardous reactions

Not available.

10.4 Conditions to avoid High temperatures, or direct sunlight.

10.5 Incompatible materials Strong acids, alkalis, and oxidising agents.

10.6 Hazardous decomposition

products

Not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

(a) Acute toxicity Based on available data on the ingredients, the classification criteria are

not met for the oral route.

Epoxy resin: LD₅₀ (oral, rat, method OECD 420) > 2000 mg/kg.

(b) Skin corrosion/irritation Based on available data on the ingredients, the classification criteria are

met for Category 2 (causes skin irritation).

Epoxy resin: may cause irritation.

(c) Serious eye Based on available data on the ingredients, the classification criteria are

met for Category 2 (causes serious eye irritation).

Epoxy resin: may cause serious eye irritation.

(d) Respiratory or skin

damage/irritation

sensitisation

Respiratory sensitisation: no relevant ingredient has been classified for

this effect.

Dermal sensitisation: based on available data, the classification criteria

are met for Category 1 (may cause an allergic skin reaction).

Epoxy resin: may cause skin sensitisation.

(e) Germ cell mutagenicity Based on available data, the classification criteria are not met.

No relevant ingredient has been classified for this effect.

Milliput Component A Page 6 of 7

SAFETY DATA SHEET

Revision: 2 May 2022 Version number: 1.0

Carcinogenicity Based on available data, the classification criteria are not met. No relevant ingredient has been classified for this effect. (g) Reproductive toxicity Based on available data, the classification criteria are not met. No relevant ingredient has been classified for this effect. (h) STOT-single exposure Based on available data, the classification criteria are not met. No relevant ingredient has been classified for this effect. STOT-repeated Based on available data, the classification criteria are not met. exposure No relevant ingredient has been classified for this effect. Aspiration hazard Based on available data, the classification criteria are not met. No relevant ingredient has been classified for this effect. 11.2 Information on other Not available. hazards

SECTION 12: Ecological information

12.1 Toxicity Based on available data, the classification criteria are met for Aquatic

Chronic Category 2 (toxic to aquatic life with long lasting effects).

Epoxy resin: toxic to aquatic organisms with long lasting effects: EC₅₀

Epoxy resin: not readily biodegradable, but hydrolyses in water (82% over

(Daphnia, 48 h) 1 mg/L; EC₅₀ (algae, 72 h) 9 mg/L.

12.2 Persistence and

degradability

Not available.

28 d).

12.3 Bioaccumulative potential

12.4 Mobility in soil

Not available.

12.5 Results of PBT and

vPvB assessment

No ingredients have been identified as PBT or vPvB.

12.6 Endocrine disrupting

properties

No ingredients have been identified as an endocrine disruptor.

12.7 Other adverse effects

The mixture is not classified as hazardous to the ozone layer.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Small consumer items may be disposed of in landfill.

For bulk disposal, incineration or landfill is recommended for this product.

Disposal via the drains is not recommended.

Chemical residues generally count as special waste. General EU requirements are given in Directive 2008/98/EC and GB equivalent.

SECTION 14: Transport information

14.1 UN Number UN 3082.

14.2 UN proper shipping

name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N O S (contains 4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane).

Milliput Component A Page 7 of 7

SAFETY DATA SHEET

Revision: 2 May 2022 Version number: 1.0

14.3 Transport hazard class(es)

9.

14.4 Packing group

III.

14.5 Environmental hazards

Marine pollutant/environmentally hazardous.

14.6 Special precautions for

user

Not available.

14.7 Maritime transport in bulk according to IMO instruments Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK: Control of Substances Hazardous to Health Regulations 2002 (COSHH), as amended.

COSHH Essentials: Easy Steps to Control Chemicals; HSE Books 2003 (also available on the HSE web site).

Workplace Exposure Limits EH40/2005 (Second edition, published

2011), Health and Safety Executive.

15.2 Chemical safety assessment

Not available.

SECTION 16: Other information

Revisions This SDS is the first version in EU format (Regulation 2020/878), using

classification according to the CLP Regulation, or GB equivalent.

Abbreviations DMEL, derived minimum effect level; DNEL, derived no-effect level; EC,

effect concentration; LD, lethal dose; OECD, Organisation for Economic Co-operation and Development; PBT, persistent, bioaccumulative, and toxic; PNEC, predicted no-effect concentration; STOT RE, specific target organ toxicity, repeated exposure; STOT SE, specific target organ toxicity, single exposure; TWA, time-weighted average; vPvB, very persistent, very bioaccumulative; WEL, UK workplace exposure limit.

References Search for chemicals; available at the European Chemicals Agency

(ECHA) website: http://echa.europa.eu/.

Basis of classification The classification of the mixture has been assessed according to the

criteria given in Regulation 1272/2008 or GB equivalent on the basis of

available information on the ingredients.

List of hazard statements H315: Causes skin irritation; H317: May cause an allergic skin reaction;

H319: Causes serious eye irritation; H411: Toxic to aquatic life with long

lasting effects.